

PF100CSW

FILM DATA SHEET



1435 S GROVE AVE #1
ONTARIO, CA 91761-4590
(844) 857-8277
PackFreshUSA.com

Physical Description:
Transparent Gloss Lamination

Physical Properties:

Backing: Biaxially oriented polypropylene
Adhesive: Pressure sensitive emulsion acrylic

PROPERTIES	TEST METHOD	UNIT OF MEASURE	TYPICAL VALUE
TOTAL THICKNESS	Caliper	mils	0.95
FILM THICKNESS	-	mils	0.7
ADHESIVE THICKNESS	-	mils	0.25
ADHESION TO STEEL	ASTM D-3330	oz/in	12
TENSILE STRENGTH	ASTM D-3759	lb/in	14
ELONGATION	ASTM D-3759	%	140
SERVICE TEMP	-	Fahrenheit	0°F to 200°F
APPLICATION TEMP	-	Fahrenheit	32°F to 150°F

The values indicated in this document are the results of tests made in compliance with normal standards. They are given as an indication and should be considered as average values. Safeguard Brands, Inc. and PackFreshUSA make no warranty, expressed or implied, as to the suitability of these materials for any specific use. The values shown above were developed from random samples taken from production material. Actual values may vary somewhat from those depicted here. Customers should determine product suitability for their applications based upon their own testing and internal criteria.