

Selfwound Overlamination

Product Description	#100 Polypropylene, Clear, Economy				
Construction	Fil Film	Adhesive	Overall Thickness	Film Thickness	Adhesive Thickness
	Biaxially Oriented Polypropylene	Emulsion Acrylic	.95 mil	0.71 mil ± 3%	0.24 mil ± 3%
Physical Properties	Note: The following technical information and data should be considered representative or typical only.				
	Tensile Strength		16 lbs/in		
	Elongation at Break		150%		
	180° Peel Adhesion		19 oz/in		
Special Features	• Resistant to UV light • Excellent resistance to chemical and abrasion • Release coating added for smooth and even unwind				
Temperature Range	Application Temperature		Operating Temperature		
	32° F to 150° F		0° F to 200° F nominal range		
Web Width	60.5"				
Standard Length	5,000'				
Government Specs.	21CFR177-1520 for indirect food contact				

Note to buyer: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. Before using, user shall determine suitability of the product for the product for its intended use and user assumes all risk and liability whatsoever in connection therewith. Seller neither makes, nor shall be bound by any warranty, expressed, implied, statutory or otherwise. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.