

PF300NP

FILM DATA SHEET



1435 S GROVE AVE #1
ONTARIO, CA 91761-4590
(844) 857-8277
PackFreshUSA.com

Exterior

60 gauge BIAx Nylon
2.4 mil LLDPE

Interior

Physical Description:

Clear 3 mil BIAx Nylon/Poly laminated barrier film

Application:

PF300NP is a very strong and clear material designed for tough food and industrial applications. Its high nylon content enables it to be used in critical vacuum applications that require strength and impact resistance. This film is sturdier than other 3 mil vacuum films due to the orientation of layers during the laminating process.

Converting:

It can be converted in many ways: 2-seal pouch, 3-seal pouch, Stand-Up Pouch, tubing or a re-closeable zippered pouch (tamper-evident or open top). It can also be surface printed or reverse trapped, and is available in web widths up to 60 inches.

Physical Properties:

PROPERTIES	TEST METHOD	UNIT OF MEASURE	TYPICAL VALUE
CALIPER		mils	3.0
YIELD		in ² /lb	10.300
MVTR	MOCON	g/100in ² 24 hrs.	0.5
OTR	MOCON	cc/100in ² /24 hrs.	3.65
BURST	MULLEN	psi	55
TENSILE MD	ASTM D-882	lbs	18
TENSILE XMD	ASTM D-882	lbs	21
TEAR MD	ASTM 689	lbs	64
TEAR XMD	ASTM 689	lbs	64

The values indicated in this document are the results of tests made in compliance with normal standards. They are given as an indication and should be considered as average values. Safeguard Brands, Inc. and PackFreshUSA make no warranty, expressed or implied, as to the suitability of these materials for any specific use. The values shown above were developed from random samples taken from production material. Actual values may vary somewhat from those depicted here. Customers should determine product suitability for their applications based upon their own testing and internal criteria.