

PF300NPW

FILM DATA SHEET



1435 S GROVE AVE #1
ONTARIO, CA 91761-4590
(844) 857-8277
PackFreshUSA.com

Exterior
60 gauge BIAx Nylon
2.4 mil White LLDPE
Interior

Physical Description:

White 3mil BIAx Nylon/Poly laminated barrier film

Application:

PF300NPW is a very strong White Material designed for tough food and industrial applications. Its high nylon content enables it to be used in critical vacuum applications that require strength and impact resistance. This FDA approved film does not stretch due to the orientation of layers during the laminating process.

Converting:

It can be converted in many ways: 2-seal pouch, 3-seal pouch, side gusset, stand up pouch and tubing. Features include: reclosable zipper, tear notch, round hang hole, and sombrero hang hole. The PF300NPW can also be surface printed or reverse-trapped printed. It is available in web widths to 60"

Physical Properties:

PROPERTIES	TEST METHOD	UNIT OF MEASURE	TYPICAL VALUE
Caliper		mils	3.0
Yield		sq.In/Lb	10,300
MVTR	Mocon	gms/100 sq. in./24 hrs	.386
OTR	Mocon	cc/100 sq. in./24 hrs	3.65
Burst	Mullen	psi	55
Tensile MD	ASTM D-882	lbs. at break	18
Tensile XMD	ASTM D-882	lbs. at break	21
Tear MD	ASTM 689	lbs. at break	64
Tear XMD	ASTM 689	lbs. at break	64

The values indicated in this document are the results of tests made in compliance with normal standards. They are given as an indication and should be considered as average values. Safeguard Brands, Inc. and PackFreshUSA make no warranty, expressed or implied, as to the suitability of these materials for any specific use. The values shown above were developed from random samples taken from production material. Actual values may vary somewhat from those depicted here. Customers should determine product suitability for their applications based upon their own testing and internal criteria.