
FILM DATA SHEET



1435 S GROVE AVE #1 ONTARIO, CA 91761-4590 (844) 857-8277 www.packfreshusa.com



Physical Description:

Clear cast deep diamond embossed 3.5mil Nylon/Poly vacuum barrier film

Application:

StaVAC is a cost-effective FDA approved film used extensively for demanding home vacuum applications. It was developed specifically to be used with home vacuum machines that cannot function with a flat "industrial grade" vacuum bag. The StaVAC deep diamond embossed material is employed on one side of the pouch, while the other side can be one of many different material options to customize the pouch to specific application requirements. The film's extensibility (ability to stretch) allows it to conform to unique product geometry for a tight vacuum. Low oxygen transfer rate, high impact resistance, and its low cost make it popular with meat, fish, cheese, nuts, dried fruit, jerky, and other snack packaging. It can also be used in boilable applications to 30 minutes of exposure.

Physical Properties:

| PROPERTIES | TEST METHOD | UNIT OF MEASURE | VALUE |
|--------------------------|----------------------|----------------------------|----------|
| Standard thickness | | Mils | 3.5 nom. |
| Yield | | in ² /lb. | 8,600 |
| Oxygen Transmission | D-3985 (@73F/0%rh) | cc/100 in ² day | 6.25 |
| Water Vapor Transmission | F-1249 (@100F/90%rh) | g/100 in ² day | 0.69 |
| Embossed Pattern | | mil | 12.5 |
| Tensile, Strength | | | |
| MD | | psi | 4,500 |
| TD | | psi | 3,500 |
| Tensile, Elongation | | | |
| MD | | percent | 400 |
| TD | | percent | 425 |
| Elmendorf Tear | | | |
| MD | | Lbf | 0.20 |
| TD | | Lbf | 0.70 |

Safeguard Brands, Inc. and PackFreshUSA make no warranty, expressed or implied, as to the suitability of these materials for any specific use. Customers should determine product suitability for their applications based upon their own testing and internal criteria.